

Laminators Approved Materials

Effective July 26, 2021

• Silicone Caulk

- Pecora PCS, 860, 890NST, 895, 896 (*color-matched Pecora 890NST available from Laminators Inc.**)
- Dow Corning® 756, 790, 795, 983, 995
- Novaflex® Metal Roof Sealant (*available from Laminators Inc.**)

***Note:** Minimum order quantities required for certain color-matched caulks

• Panel Adhesive

- Chem Link™ WallSecure™ (*available from Laminators Inc.*)
- Pecora 896 * (**Tru White**) (*available from Laminators Inc.*)

***Note:** For use in installations requiring Miami-Dade or cold-weather applications with ambient temperatures ranging from 32° F to -20° F.

• Fabrication Sealant (*refer to TB-1007 for product applications*)

- Sikaflex®-11 FC (*available from Laminators Inc.*)
- Pecora 896 (**Translucent only**) (*available from Laminators Inc.*)

• Screws and Specialty Fasteners

- Refer to Laminators CAD Drawings (available at www.LaminatorsInc.com) for fastener size, spacing requirements, and available part numbers for all Laminators' installation systems
- **Note:** Screws and specialty fasteners for use with Back-Drained and Ventilated, Field-Fabricated Installation Systems (1-Piece, Tight-Fit Molding and Clip & Caulk) and Omega CI® Rigid Insulation Panels are available from Laminators Inc.

• Air and Water Barrier

The following products have been tested with Laminators' installation systems as follows:

- Carlisle® Fire Resist Barritech VP
 - *NFPA 285 compliance for Back-Drained and Ventilated Field-Fabricated Installation Systems (1-Piece, Tight Fit Molding and Clip & Caulk)*
- Henry® Air-Bloc® 31MR
 - *NFPA 285 compliance for Dry Seal Shop-Fabricated Installation System*
 - *Miami-Dade Notice of Acceptance (NOA)*
- Henry® Air-Bloc® 33MR
 - *NFPA 285 compliance for Rout & Return Shop-Fabricated Installation System*

This document replaces any previous version published by Laminators Incorporated.

Trademarks are registered by the companies listed.