LAMINATORS
Composite Panel Solutions

www.LaminatorsInc.com
800.523.2347
3255 Penn St, Hatfield, PA 19440

OMEGA-LITE® FR
TECHNICAL DATA SHEET

PRODUCT: Omega-Lite FR

EFFECTIVE: November 17, 2026

Description: Laminators Inc. Omega-Lite FR is an aluminum composite material (ACM) panel that consists of a thermoplastic core with nonhalogenated, fire-resistant (FR) additive bonded to a texture/color finished sheet of aluminum on one face and a protected mill finished sheet of aluminum on the other. Panels are intended for use in various Laminators Inc. installation systems.

Properties:

Thickness	6 mm (nom)
Weight	0.90 psf (+/-)
Core	Extruded Corrugated Polypropylene with Nonhalogenated FR Additive
Aluminum Sheets [1] (ASTM B209)	3105-H24 & H28; 5005-H34 0.012 to 0.032 in
Texture Finish	Smooth
Color Finish (AAMA 2605)	PVDF/Kynar 500®, Polyester, or Anodized
Coefficient of Thermal Expansion, α	$13x10^{-6}$ in/in/°F

Performance:

Combustibility Classification (ASTM D635)	Class CC2
Self-Ignition Temperature (ASTM D1929)	Greater than 800°F
Average Peel Torque (ASTM D1781)	28.24 in-lb/in
Fire Performance (ASTM E84)	Class A

Notes:
1. Panels include 0.012 in (min) actual sheet thickness backer and 0.024 in (min) actual sheet thickness facer.