

Laminators Approved Materials

Effective February 23, 2022

Silicone Caulk

- Pecora PCS, 860, 890NST, 890FTS 895, 896 (*color-matched Pecora 890NST available from Laminators Inc.**)
 - Dow Corning® 756, 790, 795, 983, 995
 - Novaflex® Metal Roof Sealant (*available from Laminators Inc.**)
- * **Note:** *Minimum order quantities required for certain color-matched caulks.*

Panel Adhesive

- Chem Link™ WallSecure™ (*available from Laminators Inc.*)
 - Pecora 896 * (**Tru White**) (*available from Laminators Inc.*)
- * **Note:** *For use in installations requiring Miami-Dade or cold-weather applications with ambient temperatures ranging from 32° F to -20° F.*

Fabrication Sealant (*refer to TB-1007 for product applications*)

- Sikaflex®-11 FC (*available from Laminators Inc.*)
- Pecora 896 (**Translucent only**) (*available from Laminators Inc.*)

Screws and Specialty Fasteners

- Refer to Laminators CAD Drawings (available at www.LaminatorsInc.com) for fastener size, spacing requirements, and available part numbers for all Laminators' installation systems
- Screws and specialty fasteners for use with Back-Drained and Ventilated, Field-Fabricated Installation Systems (1-Piece, Tight-Fit Molding and Clip & Caulk) and Omega CI® Rigid Insulation Panels are available from Laminators Inc.

Air and Water Barrier (*may require EEV from Laminators for compliance with NFPA 285*)

- Carlisle® Fire Resist Barritech VP
- Henry® Air-Bloc® 16MR, 17MR, 31MR, 33MR (*31MR & 33MR have been discontinued by manufacturer*)
- Other products available upon request

This document replaces any previous version published by Laminators Incorporated.
Trademarks are registered by the companies listed.