Laminators Approved Materials for Legacy Systems

Effective February 23, 2022

Silicone Caulk

- Pecora PCS, 860, 890NST, 890FTS 895, 896 *(color-matched Pecora 890NST available from Laminators Inc.*)*
- Dow Corning® 756, 790, 795, 983, 995
- Novaflex® Metal Roof Sealant *(available from Laminators Inc.*)*
  * **Note:** *Minimum order quantities required for certain color-matched caulks.*

Panel Adhesive

- Chem Link™ WallSecure™ *(available from Laminators Inc.)*
- Pecora 896 * (**Tru White**) *(available from Laminators Inc.)*
  * **Note**: *For use in installations requiring Miami-Dade or cold-weather applications with ambient temperatures ranging from 32° F to -20° F.*

Fabrication Sealant *(refer to TB-1007 for product applications)*

- Sikaflex®-11 FC *(available from Laminators Inc.)*
- Pecora 896 (**Translucent only**) *(available from Laminators Inc.)*

Fasteners

- Fastener size and spacing to be based on project-specific wind loads. Refer to Laminators installation system CAD Drawings (available at www.LaminatorsInc.com) or contact Technical Support at 800.523.2347 for additional information.

Air and Water Barrier

- Henry® Air-Bloc® 16MR, 17MR, & 31MR *(31MR has been discontinued by manufacturer)*

Important Notices:

1. Application thickness and substrate preparation for air and water barrier products to comply with manufacturer's installation requirements.
2. Application of panel adhesive directly to listed air and water barrier products is only permissible over plywood sheathing.
3. For all other air and water barrier products OR installations over OSB and gypsum sheathing:
   - Install 4" x 4" cold-formed strapping squares (18 ga. min) at each discrete adhesive location fastened to structure using (3) #8 fasteners per strapping square, and
   - Install continuous 4" wide cold-formed strapping (18 ga. min) along all adhesive lines (as required for Clip & Caulk) per Laminators CAD Drawings

Go beyond the panel… and go to the next level!